



Beam clamps for Roller Supports, Type PKR

Material:	S235, clamps GS 45, threaded parts 8.8 / 8, hot-dip galvanized
Vorspannung:	M12 - 30 Nm, M16 - 60 Nm, M20 - 90 Nm
Finish:	complete, incl. nuts, hot-dip galvanized

Article no.	beam dimensions A B [mm]	thread rod C [mm]			insert for roller support F_z [kN]	weight per set [kg]
PKR-120/12-F	100 - 120	8 - 19	180		4 - 25	1,0
PKR-160/12-F	130 - 160	8 - 19	220			1,2
PKR-200/12-F	170 - 200	8 - 19	260			1,4

Article no.	beam dimensions A B [mm]	thread rod C [mm]			insert for roller support F_z [kN]	weight per set [kg]
PKR-160/16-F	130 - 160	8 - 19	260		50	2,1
PKR-200/16-F	170 - 200	8 - 19	300			2,1
PKR-240/16-F	210 - 240	8 - 19	340			4,4
PKR-300/16-F	260 - 300	8 - 19	400			4,6

Article no.	beam dimensions A B [mm]	thread rod C [mm]			insert for roller support F_z [kN]	weight per set [kg]
PKR-160/20-F	130 - 160	8 - 19	260		100	6,2
PKR-200/20-F	170 - 200	8 - 19	300			6,4
PKR-240/20-F	210 - 240	8 - 19	340			6,6
PKR-300/20-F	260 - 300	8 - 19	400			6,8

Ordering example: RKR-160/12-F

- Steel parts hot-dip galvanized
- Thread rod \varnothing
- Beam width 130 - 160 mm, z.B. HEA 160
- Beam clamps for roller support Type PKR