



### Roller Supports, Type REU without guide

<b>Material:</b>	Roller: <b>S235</b> ; pin: <b>1.4571</b> ; sheeks: <b>S235JR</b>
	Bearing bush: composite bearing made of sintered bronze / PTFE for dry running in difficult conditions
<b>Finish:</b>	Steel parts hot-dip galvanized

Article no.	support load $F_z$ [kN]	L [mm]	A [mm]	H [mm]	B [mm]	C [mm]	beam clamps		weight [kg]
							Typ		
REU-080/15-F	15	80	146	65	60	60	M12		3,0
REU-100/15-F	15	100	166	65	60	60	M12		3,2
REU-120/15-F	15	120	186	65	60	60	M12		3,5
REU-140/15-F	15	140	206	65	60	60	M12		3,7
REU-080/25-F	25	80	146	80	70	75			5,0
REU-100/25-F	25	100	166	80	70	75	M12		5,4
REU-120/25-F	25	120	186	80	70	75	M12		5,8
REU-140/25-F	25	140	206	80	70	75	M12		6,3
REU-080/50-F	50	80	146	100	100	95	M16		9,2
REU-100/50-F	50	100	166	100	100	95	M16		10,3
REU-120/50-F	50	120	186	100	100	95	M16		11,1
REU-140/50-F	50	140	206	100	100	95	M16		11,9
REU-200/100-F	100	200	266	125	130	110	M20		23,8

**Ordering example:** REU-100/50-F

- Steel parts hot-dip galvanized
- Support load 50 kN
- Roller length: 100 mm
- Roller support Type REU, without guide

Notes: Mounting of the roller bearings on steel constructions with profile clamps type PKR, see page 17