



### Roller Supports, Type RKP with polyamide taper roll

<b>Material:</b>	Roller: <b>Polyamide</b> ; pin: <b>1.4571</b> ; sheeks: <b>S235JR</b>
<b>Finish:</b>	Steel parts hot-dip galvanized

Article no.	support load $F_z$ [kN]	suitable for pipe diameter	L [mm]	A [mm]	H [mm]	Y [mm]	beam clamps Typ	weight [kg]
RKP-004-F	4,0	115 - 273	120	186	90	70	M12	3,0
RKP-008-F	8,0	220 - 324	140	206	100	75	M12	5,0
RKP-015-F	15,0	273 - 458	200	266	135	100	M12	8,0

### Roller Supports, Type RKS with steel taper roll

<b>Material:</b>	Roller: <b>S235</b> ; pin: <b>1.4571</b> ; sheeks: <b>S235JR</b>
	Bearing bush: composite bearing made of sintered bronze / PTFE for dry running in difficult conditions
<b>Finish:</b>	Steel parts hot-dip galvanized

Article no.	support load $F_z$ [kN]	suitable for pipe diameter	L [mm]	A [mm]	H [mm]	Y [mm]	beam clamps [mm]	weight [kg]
RKS-008-F	8,0	115 - 273	120	186	90	70	M12	6,2
RKS-015-F	16,0	220 - 324	140	206	100	75	M12	8,0
RKS-050-F	50,0	273 - 458	200	266	135	100	M16	15,0

**Ordering example:** RKS-008-F

- └ Steel parts hot-dip galvanized
- └ Support load 8 kN
- └ Roller support Type RKS with steel taper roll

Notes: Mounting of the roller bearings on steel constructions with profile clamps type PKR, see page 17